



# Shell Sterak Grease 1

Shell Sterak Grease 1 is a lithium base grease specially blended for use in steering boxes in all types of vehicles. It has excellent low temperature properties being suitable for use in steering boxes down to -40°C. It is an NLGI 1 consistency grease, with enhanced anti-wear and anti-corrosion properties.

## Typical Physical Characteristics

<b>Shell Sterak Grease 1</b>	
<b>Soap Type</b>	Lithium
<b>Base Oil</b>	
<b>Kinematic Viscosity</b>	
@ 40 °C cSt	100
100 °C cSt	11.0
(IP 71)	
<b>NLGI Consistency</b>	1
<b>IP Penetration</b>	310-340
(IP 50)	
<b>Dropping Point °C</b>	
(IP 132)	175
<b>Four-ball weld load kg</b>	
(IP 239)	190 min

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Shell Sterak Grease 1 is unlikely to present any significant health or safety hazard when properly used in the recommended application, and good standards of industrial and personal hygiene are maintained.

For further guidance on Product Health & Safety refer to the appropriate Shell Product Safety Data Sheet. This can be obtained from your own internal Health & Safety focal point. In the event of any queries contact your local Shell Business Development Manager or:

### Normal Office Hours

Shell UK Oil Products Ltd  
Delta House  
Wavell Road  
Wythenshawe  
Manchester M22 5SB  
Tel: 0161 499 4000

### Emergencies

Shell UK Oil Products Ltd  
Shell Centre  
London  
SE1 7NA  
Tel: 020 7934 1234